

Applic. No. 09/745,563

Amdt. dated January 10, 2005

Reply to Office action of October 8, 2004

Claim Amendments

This listing of the claims will replace all prior versions, and listings, of claims in the application:

Claim 1 (currently amended): A guide apparatus for guiding sheets in a transport direction to a sheet-processing machine, including a printing machine, comprising:

a guide element to be disposed above a feed table;

a height-adjusting device connected to said guide element for adjusting a distance between said guide element and the feed table, said height-adjusting device having a first drive and a second drive which can be actuated independently of each other; and

~~a lifting device~~ third drive connected to said guide element for ~~displacing~~ pivoting said guide element in and opposite to the sheet transport direction.

Claim 2 (original): The guide apparatus according to claim 1, wherein said first drive and said second drive can be coupled to each other.

Applic. No. 09/745,563

Amdt. dated January 10, 2005

Reply to Office action of October 8, 2004

Claim 3 (original): The guide apparatus according to claim 1, wherein said first drive is a piston/cylinder unit.

Claim 4 (original): The guide apparatus according to claim 3, including a guide on which said guide element is supported, said piston/cylinder unit having a cylinder disposed in a fixed location and a piston rod which passes through said cylinder, said piston rod having an first end interacting with said guide and a second end.

Claim 5 (original): The guide apparatus according to claim 4, wherein said second drive has an actuating element interacting with said second end of said piston rod and an actuating motor interacting with said actuating element for displacing said actuating element in a direction of a longitudinal mid-axis of said piston rod.

Claim 6 (original): The guide apparatus according to claim 5, wherein said piston rod and said actuating element are disposed so as to be aligned.

Claim 7 (original): The guide apparatus according to claim 4, including a foreign-body protective apparatus which, in order to enlarge said distance between the guide element and the

Applic. No. 09/745,563

Amdt. dated January 10, 2005

Reply to Office action of October 8, 2004

feed table, activates at least one of said first drive and said second drive of said height-adjusting device.

Claim 8 (original): The guide apparatus according to claim 7, wherein said foreign-body protective apparatus activates said first drive when a force is exceeded which is directed away from the feed table (3) in a vertical direction and acts on said guide.

Claim 9 (original): The guide apparatus according to claim 4, including a cross-member connected to said guide and said guide element is disposed on said cross-member, said cross-member can be pivoted about an axis running transversely with respect to a sheet transport direction.

Claim 10 (currently amended): The guide apparatus according to claim 9, wherein said ~~lifting device~~ third drive pivots said cross-member.

Claim 11 (original): The guide apparatus according to claim 9, wherein said guide can be displaced in a vertical direction by said height adjusting device and has racks, including a first rack and a second rack, disposed on a drive and operator side of the sheet-processing machine and on which said cross-member is to be pivotably mounted.

Applic. No. 09/745,563
Amdt. dated January 10, 2005
Reply to Office action of October 8, 2004

Claim 12 (original): The guide apparatus according to claim 11, including a rotatable geared shaft disposed in a fixed location, and said racks mesh with said rotatable geared shaft.

Claim 13 (original): The guide apparatus according to claim 11, including a third rack coupled to said guide and connected to said piston rod.

Claim 14 (original): The guide apparatus according to claim 9, wherein said guide element is clamped to said cross-member, and a distance between said guide element and a longitudinal mid-axis of said cross-member can be set.

Claim 15 (original): The guide apparatus according to claim 14, wherein said guide element is one of a number of guide elements disposed at a distance from one another and fixed to said cross-member, and it being possible to set a distance from the longitudinal mid-axis of said cross-member individually.

Claim 16 (original): The guide apparatus according to claim 1, wherein said guide element is a separating roller having a convex configuration.

Applic. No. 09/745,563

Amdt. dated January 10, 2005

Reply to Office action of October 8, 2004

Claim 17 (original): The guide apparatus according to claim 9, wherein said cross-member is a front lay guard.

Claim 18 (original): The guide apparatus according to claim 17, including a vertically adjustable brush disposed on said front lay guard.

Claim 19 (original): The guide apparatus according to claim 3, wherein said piston/cylinder unit is a pneumatic piston/cylinder unit.

Claim 20 (withdrawn): A method for feeding signatures to a sheet-processing machine in a transport direction, including a printing machine, which comprises the steps of:

providing a guide apparatus having a guide element to be disposed above a feed table and a height-adjusting device connected to the guide element for adjusting a distance between the guide element and the feed table, the height-adjusting device having a first drive and a second drive which can be actuated independently of each other, and a third drive connected to the guide element for pivoting the guide element in and opposite to the transport direction;

Applic. No. 09/745,563

Amdt. dated January 10, 2005

Reply to Office action of October 8, 2004

disposing the guide apparatus, as viewed in a transport direction of sheets, upstream of a front lay, the sheets being fed to the guide apparatus in an underlapped form;

placing the guide element at a distance from the front lay when an initial sheet of a stream of sheets runs in the guide element as viewed in the transport direction of the sheets; and

enlarging the distance between the guide element and the front lay for following sheets of the stream of sheets.

Claim 21 (withdrawn): The method according to claim 20, which comprises automatically changing the distance between the guide element and the feed table and the distance between the guide element and the front lay.

Claim 22 (withdrawn): The method according to claim 21, which comprises setting the distance between the front lay and the guide element steplessly.

Claim 23 (currently amended): A guide apparatus for guiding sheets in a transport direction to a sheet-processing machine, including a printing machine, comprising:

Applic. No. 09/745,563

Amdt. dated January 10, 2005

Reply to Office action of October 8, 2004

a guide element to be disposed above a feed table; and

a height-adjusting device connected to said guide element for adjusting a distance between said guide element and the feed table, said height-adjusting device having a first vertical drive and a second vertical drive which can be actuated independently of each other; and

a ~~lifting device~~ third drive connected to said guide element for ~~displacing~~ pivoting said guide element in and opposite to the sheet transport direction.